

Network Working Group
Request for Comments: 1749
Updates: 1748
Category: Standards Track

K. McCloghrie
F. Baker
E. Decker
cisco Systems, Inc.
December 1994

IEEE 802.5 Station Source Routing MIB using SMIV2

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Table of Contents

1. Introduction	1
2. The SNMPv2 Network Management Framework	2
2.1 Object Definitions	2
3. Overview	2
3.1 Source Routing	2
3.2 Relationship to RFC 1748	3
3.3 Relationship to RFC 1525	3
3.4 Static Source Routes	4
3.5 Destinations on the Local Ring	4
4. Definitions	4
5. Acknowledgements	8
6. References	8
7. Security Considerations	9
8. Authors' Addresses	10

1. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used by IEEE 802.5 end-stations for managing source routes on a Token Ring network where IEEE source-routing is in use. IEEE source-routing is described in 802.5 Token Ring Access Method and Physical Layer Specifications [8] and related ISO publications [9, 10, 11].

This memo is an incremental update to RFC 1748 [6]. It is documented separately from the RFC 1748 solely due to the latter's maturity within the Internet standardization process.

2. The SNMPv2 Network Management Framework

The SNMPv2 Network Management Framework consists of four major components. They are:

- o RFC 1442 [1] which defines the SMI, the mechanisms used for describing and naming objects for the purpose of management.
- o STD 17, RFC 1213 [2] defines MIB-II, the core set of managed objects for the Internet suite of protocols.
- o RFC 1445 [3] which defines the administrative and other architectural aspects of the framework.
- o RFC 1448 [4] which defines the protocol used for network access to managed objects.

The Framework permits new objects to be defined for the purpose of experimentation and evaluation.

2.1. Object Definitions

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the subset of Abstract Syntax Notation One (ASN.1) defined in the SMI. In particular, each object type is named by an OBJECT IDENTIFIER, an administratively assigned name. The object type together with an object instance serves to uniquely identify a specific instantiation of the object. For human convenience, we often use a textual string, termed the descriptor, to refer to the object type.

3. Overview

This memo defines a single table: the 802.5 Station Source Routing Table, which contains the source routes known by a end-station on an IEEE 802.5 Token Ring network in which IEEE source-routing is in use.

3.1. Source Routing

Source routing extends the 802.5 protocol [8] by assigning a unique ring number to each ring within the extended LAN, and a bridge number to each source routing bridge's connection to a ring. A Routing Information Field (RIF) must be included in frames which need to traverse multiple rings. The format of the RIF is:

3.4. Static Source Routes

It is unclear how many, if any, existing systems allow the creation or deletion of "static" 802.5 source routes by network management. However, SNMPv2 SMI defines that the MAX-ACCESS clause as specifying the maximal level of access which makes "protocol sense". Thus, this memo provides support for static source routes through the dot5SrRouteStatus object, but the conformance statements allow for stations which do not support static source routes, by requiring that compliant agents only need provide read-access to dot5SrRouteStatus.

3.5. Destinations on the Local Ring

Entries should be included in the dot5SrRouteTable for destination MAC addresses which are on the same ring as the instrumented 802.5 interface. For such entries, dot5SrRouteDescr has the value of the zero-length string, and dot5SrRouteControl has the corresponding value.

4. Definitions

TOKENRING-STATION-SR-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE

FROM SNMPv2-SMI

TEXTUAL-CONVENTION, RowStatus, MacAddress

FROM SNMPv2-TC

MODULE-COMPLIANCE, OBJECT-GROUP

FROM SNMPv2-CONF

mib-2, ifIndex

FROM RFC1213-MIB;

dot5SrMIB MODULE-IDENTITY

LAST-UPDATED "9412161000Z"

ORGANIZATION "IETF Interfaces MIB Working Group"

CONTACT-INFO

" Keith McCloghrie
Postal: Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
US

Phone: +1 408 526 5260

Email: kzm@cisco.com"

DESCRIPTION

"The MIB module for managing source routes in
end-stations on IEEE 802.5 Token Ring networks."

::= { mib-2 42 }

```
dot5SrMIBObjects OBJECT IDENTIFIER ::= { dot5SrMIB 1 }
```

```
SourceRoute ::= TEXTUAL-CONVENTION
```

```
    DISPLAY-HINT "1x:"
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "Represents a Source Route, containing an
        embedded sequence of bridge and ring ID's,
        as used by 802.5 Source Routing."
```

```
    REFERENCE  "Annex C of ISO/IEC 10038: 1993,
                [ANSI/IEEE Std 802.1D, 1993]"
```

```
    SYNTAX      OCTET STRING (SIZE(0..30))
```

```
--          The 802.5 Station Source Route Table
--
```

```
dot5SrRouteTable OBJECT-TYPE
```

```
    SYNTAX      SEQUENCE OF Dot5SrRouteEntry
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "The table of source-routing routes.
```

```
        This represents the 802.5 RIF database."
```

```
    ::= { dot5SrMIBObjects 1 }
```

```
dot5SrRouteEntry OBJECT-TYPE
```

```
    SYNTAX      Dot5SrRouteEntry
```

```
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
```

```
    DESCRIPTION
```

```
        "Information on a specific route.
```

```

        An entry is created whenever a 'Single Path
        Explorer' or an 'All Paths Explorer' discovers
        a route to a neighbor not currently in the table,
        or whenever an 'All Paths Explorer' discovers a
        better (e.g., shorter) route than the route currently
        stored in the table.  This is done on behalf of
        any network layer client.
```

```

        The ifIndex value in the INDEX clause refers to
        the value of MIB-II's ifIndex object for the
        interface on which the route is in effect."
```

```
    INDEX { ifIndex, dot5SrRouteDestination }
```

```
    ::= { dot5SrRouteTable 1 }
```

```
Dot5SrRouteEntry ::= SEQUENCE {
```

```

dot5SrRouteDestination  MacAddress,
dot5SrRouteControl      OCTET STRING,
dot5SrRouteDescr        SourceRoute,
dot5SrRouteStatus       RowStatus
}

dot5SrRouteDestination OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The destination of this route."
    ::= { dot5SrRouteEntry 2 }

dot5SrRouteControl OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(2))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The value of Routing Control field for this
        route."
    REFERENCE   "Annex C of ISO/IEC 10038: 1993,
        [ANSI/IEEE Std 802.1D, 1993]"
    ::= { dot5SrRouteEntry 3 }

dot5SrRouteDescr OBJECT-TYPE
    SYNTAX      SourceRoute
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The embedded sequence of bridge and ring ID's
        for this route. For destinations on the
        local ring, the value of this object is
        the zero-length string."
    REFERENCE   "Annex C of ISO/IEC 10038: 1993,
        [ANSI/IEEE Std 802.1D, 1993]"
    ::= { dot5SrRouteEntry 4 }

dot5SrRouteStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The status of this row. Values of the instances
        of dot5SrRouteControl and dot5SrRouteDescr can be
        modified while the row's status is 'active.'"
    ::= { dot5SrRouteEntry 5 }

```

```
-- conformance information
```

```
dot5SrConformance OBJECT IDENTIFIER ::= { dot5SrMIB 2 }
```

```
dot5SrGroups      OBJECT IDENTIFIER ::= { dot5SrConformance 1 }
```

```
dot5SrCompliances OBJECT IDENTIFIER ::= { dot5SrConformance 2 }
```

```
-- compliance statements
```

```
dot5SrCompliance MODULE-COMPLIANCE
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The compliance statement for SNMPv2 entities
        which implement the IEEE 802.5 Station Source Route
        MIB."
```

```
MODULE -- this module
```

```
    MANDATORY-GROUPS { dot5SrRouteGroup }
```

```
    OBJECT      dot5SrRouteStatus
```

```
    SYNTAX      INTEGER { active(1) }    -- subset of values
```

```
    MIN-ACCESS  read-only
```

```
    DESCRIPTION
```

```
        "Write access is not required, and only the 'active'
        value need be supported."
```

```
    OBJECT      dot5SrRouteControl
```

```
    MIN-ACCESS  read-only
```

```
    DESCRIPTION
```

```
        "Write access is not required."
```

```
    OBJECT      dot5SrRouteDescr
```

```
    MIN-ACCESS  read-only
```

```
    DESCRIPTION
```

```
        "Write access is not required."
```

```
 ::= { dot5SrCompliances 1 }
```

```
-- units of conformance
```

```
dot5SrRouteGroup OBJECT-GROUP
```

```
    OBJECTS { dot5SrRouteControl,
               dot5SrRouteDescr,
               dot5SrRouteStatus
            }
```

```
    STATUS current
```

DESCRIPTION

"A collection of objects providing for the management of source routes in stations on IEEE 802.5 source-routing networks."

::= { dot5SrGroups 1 }

END

5. Acknowledgements

The need for this MIB module was agreed upon by the members of the IETF Interfaces Working Group, and the definitions were derived from experience with enterprise-specific MIBs presented to the Working Group.

6. References

- [1] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Structure of Management Information for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1442, SNMP Research, Inc., Hughes LAN Systems, Dover Beach Consulting, Inc., Carnegie Mellon University, April 1993.
- [2] McCloghrie, K., and M. Rose, Editors, "Management Information Base for Network Management of TCP/IP-based internets: MIB- II", STD 17, RFC 1213, Hughes LAN Systems, Performance Systems International, March 1991.
- [3] Galvin, J., and K. McCloghrie, "Administrative Model for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1445, Trusted Information Systems, Hughes LAN Systems, April 1993.
- [4] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Protocol Operations for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1448, SNMP Research, Inc., Hughes LAN Systems, Dover Beach Consulting, Inc., Carnegie Mellon University, April 1993.
- [5] Case, J., McCloghrie, K., Rose, M., and S. Waldbusser, "Textual Conventions for version 2 of the Simple Network Management Protocol (SNMPv2)", RFC 1443, SNMP Research Inc., Hughes LAN Systems, Dover Beach Consulting, Inc., Carnegie Mellon University, April 1993.
- [6] McCloghrie, K., and E. Decker, "IEEE 802.5 Token Ring MIB using SMIV2", RFC 1748 cisco Systems, Inc., December 1994.

- [7] McCloghrie, K., Decker, E., Langville, P., and A. Rijsinghani, "Definitions of Managed Objects for Source Routing Bridges", RFC 1525, Hughes LAN Systems, cisco Systems, Inc., Digital Equipment Corporation, September 1993.
- [8] "Token Ring Access Method and Physical Layer Specifications", IEEE Standard 802.5-1989, 1989.
- [9] "Information technology - Local and metropolitan area networks - Part 5: Token ring access method and physical layer specifications", ISO/IEC 8802-5, 1992.
- [10] "Information technology - Telecommunications and information exchange between systems - Local area networks - Media access control (MAC) bridges", ISO/IEC 10038, 1993 [ANSI/IEEE Std 802.1D, 1993 Edition].
- [11] "Source Routing Operation by End Systems", ISO/IEC 8802-2 PDAM5.3 (6N7721).

7. Security Considerations

Security issues are not discussed in this memo.

8. Authors' Addresses

Keith McCloghrie
cisco Systems, Inc.
170 West Tasman Drive,
San Jose CA 95134-1706.

Phone: (408) 526-5260
EMail: kzm@cisco.com

Fred Baker
cisco Systems, Inc.
519 Lado Drive
Santa Barbara, CA 93111

Phone: (805) 681-0115
EMail: fred@cisco.com

Eric B. Decker
cisco Systems, Inc.
1525 O'Brien Dr.
Menlo Park, California 94025

Phone: (415) 688-8241
EMail: cire@cisco.com

