

Network Working Group  
Request for Comments: 2206  
Category: Standards Track

F. Baker  
Cisco Systems  
J. Krawczyk  
ArrowPoint Communications  
A. Sastry  
Cisco Systems  
September 1997

## RSVP Management Information Base using SMIV2

### Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

### Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in TCP/IP-based internets. In particular, it defines objects for managing the Resource Reservation Protocol (RSVP) within the interface attributes defined in the Integrated Services Model. Thus, the Integrated Services MIB is directly relevant to and cross-referenced by this MIB. Comments should be made to the RSVP Working Group, [rsvp@isi.edu](mailto:rsvp@isi.edu).

### Table of Contents

1 The SNMPv2 Network Management Framework .....	2
1.1 Object Definitions .....	2
2 Overview .....	3
2.1 Textual Conventions .....	3
2.2 Structure of MIB .....	3
2.3 Semantics of Writing the Path and Reservation State Databases .....	3
2.4 Intended use of Flow Notifications .....	4
2.4.1 The lostFlow Notification .....	4
2.4.2 The newFlow Notification .....	4
3 Definitions .....	4
3.1 RSVP Session Statistics Database .....	6
3.2 RSVP Session Sender Database .....	9
3.3 RSVP Reservations Requested Database .....	25
3.4 RSVP Reservation Requests Database .....	35
3.5 RSVP Interface Attributes Database .....	44

3.6	RSVP Neighbor Database .....	48
3.7	Notifications .....	49
4	Security Considerations.....	63
5	Authors' Addresses .....	63
6	Acknowledgements .....	63
7	References .....	64

## 1. The SNMPv2 Network Management Framework

The SNMPv2 Network Management Framework consists of four major components. They are:

- o RFC 1441 which defines the SMI, the mechanisms used for describing and naming objects for the purpose of management.
- o STD 17, RFC 1213 defines MIB-II, the core set of managed objects for the Internet suite of protocols.
- o RFC 1445 which defines the administrative and other architectural aspects of the framework.
- o RFC 1448 which defines the protocol used for network access to managed objects.

The Framework permits new objects to be defined for the purpose of experimentation and evaluation.

### 1.1. Object Definitions

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. Objects in the MIB are defined using the subset of Abstract Syntax Notation One (ASN.1) defined in the SMI. In particular, each object type is named by an OBJECT IDENTIFIER, an administratively assigned name. The object type together with an object instance serves to uniquely identify a specific instantiation of the object. For human convenience, we often use a textual string, termed the descriptor, to refer to the object type.

## 2. Overview

### 2.1. Textual Conventions

Several new data types are introduced as a textual convention in this MIB document. These textual conventions enhance the readability of the specification and can ease comparison with other specifications if appropriate. It should be noted that the introduction of these textual conventions has no effect on either the syntax nor the semantics of any managed objects. The use of these is merely an artifact of the explanatory method used. Objects defined in terms of one of these methods are always encoded by means of the rules that define the primitive type. Hence, no changes to the SMI or the SNMP are necessary to accommodate these textual conventions which are adopted merely for the convenience of readers and writers in pursuit of the elusive goal of clear, concise, and unambiguous MIB documents.

### 2.2. Structure of MIB

The MIB is composed of the following sections:

- General Objects
- Session Statistics Table
- Session Sender Table
- Reservation Requests Received Table
- Reservation Requests Forwarded Table
- RSVP Interface Attributes Table
- RSVP Neighbor Table

As a general rule, it is difficult in SNMP to describe arbitrarily long or complex messages; this MIB therefore seeks to describe the Path State Database and the Reservation State Database as though each flow and filter description received in an aggregate message had been received in a separate reservation message.

Thus, if a RESV message is received for session 224.1.2.3+UDP+4455 with two filter/flow spec groups describing a sender 1.2.3.4 and another sender 1.2.7.8, these two will show in the MIB as two separate rows: one for 224.1.2.3+UDP+4455 from 1.2.3.4 and the other for 224.1.2.3+UDP+4455 from 1.2.7.8.

### 2.3. Semantics of Writing the Path and Reservation State Databases

The path and reservation state tables are writeable. Writing into the Path and Reservation State databases allows one to perform RSVP reservations without authenticating through RSVP mechanisms, but

rather through SNMP mechanisms. State created in this way by SNMP does not time out and cannot be deleted by receiving an RSVP teardown message; it can only be deleted by SNMP. Deletion is accomplished by writing 'destroy' to the associated Row Status object, and this will initiate a teardown message as if the state had timed out.

## 2.4. Intended use of Flow Notifications

### 2.4.1. The lostFlow Notification

The Lost Flow notification is an asynchronous event that signifies that a flow is no longer being observed.

### 2.4.2. The newFlow Notification

The newFlow Notification defined in this MIB can be used to advise a network management system of the state of a flow.

## 3. Definitions

RSVP-MIB DEFINITIONS ::= BEGIN

### IMPORTS

```

MODULE-IDENTITY, OBJECT-TYPE, Gauge32,
NOTIFICATION-TYPE, Integer32, mib-2
                                FROM SNMPv2-SMI
TEXTUAL-CONVENTION, TruthValue, RowStatus,
TimeStamp, TestAndIncr, TimeInterval
                                FROM SNMPv2-TC
MODULE-COMPLIANCE, OBJECT-GROUP,
NOTIFICATION-GROUP                FROM SNMPv2-CONF
Port, SessionNumber, SessionType,
Protocol, QosService, intSrvFlowStatus,
MessageSize, BitRate, BurstSize
                                FROM INTEGRATED-SERVICES-MIB
ifIndex, InterfaceIndex          FROM IF-MIB;

```

### rsvp MODULE-IDENTITY

```

LAST-UPDATED "9511030500Z" -- Thu Aug 28 09:03:53 PDT 1997
ORGANIZATION "IETF RSVP Working Group"
CONTACT-INFO
"      Fred Baker
Postal: Cisco Systems
        519 Lado Drive
        Santa Barbara, California 93111
Tel:    +1 805 681 0115
E-Mail: fred@cisco.com

```

John Krawczyk  
 Postal: ArrowPoint Communications  
 235 Littleton Road  
 Westford, Massachusetts 01886  
 Tel: +1 508 692 5875  
 E-Mail: jjk@tiac.net

Arun Sastry  
 Postal: Cisco Systems  
 210 W. Tasman Drive  
 San Jose, California 95134  
 Tel: +1 408 526 7685  
 E-Mail: arun@cisco.com"

## DESCRIPTION

"The MIB module to describe the RSVP Protocol"  
 ::= { mib-2 51 }

rsvpObjects OBJECT IDENTIFIER  
 ::= { rsvp 1 } -- tables  
 rsvpGenObjects OBJECT IDENTIFIER  
 ::= { rsvp 2 } -- global objects  
 rsvpNotificationsPrefix OBJECT IDENTIFIER  
 ::= { rsvp 3 } -- traps  
 rsvpConformance OBJECT IDENTIFIER  
 ::= { rsvp 4 } -- conformance

RsvpEncapsulation ::= TEXTUAL-CONVENTION

STATUS current

## DESCRIPTION

"This indicates the encapsulation that an RSVP Neighbor is perceived to be using."

SYNTAX INTEGER {  
     ip (1), -- IP Protocol 46  
     udp (2), -- UDP Encapsulation  
     both (3) -- neighbor is using both encapsulations  
 }

RefreshInterval ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

## DESCRIPTION

"The number of milliseconds that are expected to elapse between refreshes of path or reservation state. Unrefreshed Path or reservation state is removed after a small multiple of this period."

```
SYNTAX    INTEGER (0..'7FFFFFFF'h)
```

```
--    The RSVP Session Statistics Database displays statistics
--    relating to the number of senders and receivers in each
--    session.
```

```
rsvpSessionTable OBJECT-TYPE
```

```
SYNTAX    SEQUENCE OF RsvpSessionEntry
```

```
MAX-ACCESS not-accessible
```

```
STATUS    current
```

```
DESCRIPTION
```

```
    "A table of all sessions seen by a given sys-
    tem."
```

```
::= { rsvpObjects 1 }
```

```
rsvpSessionEntry OBJECT-TYPE
```

```
SYNTAX    RsvpSessionEntry
```

```
MAX-ACCESS not-accessible
```

```
STATUS    current
```

```
DESCRIPTION
```

```
    "A single session seen by a given system."
```

```
INDEX { rsvpSessionNumber }
```

```
::= { rsvpSessionTable 1 }
```

```
RsvpSessionEntry ::=
```

```
SEQUENCE {
    rsvpSessionNumber      SessionNumber,
    rsvpSessionType       SessionType,
    rsvpSessionDestAddr   OCTET STRING,
    rsvpSessionDestAddrLength INTEGER,
    rsvpSessionProtocol   Protocol,
    rsvpSessionPort       Port,
    rsvpSessionSenders    Gauge32,
    rsvpSessionReceivers  Gauge32,
    rsvpSessionRequests   Gauge32
}
```

```
rsvpSessionNumber OBJECT-TYPE
```

```
SYNTAX    SessionNumber
```

```
MAX-ACCESS not-accessible
```

```
STATUS    current
```

```
DESCRIPTION
```

```
    "The number of this session. This is for SNMP
```

Indexing purposes only and has no relation to any protocol value."  
 ::= { rsvpSessionEntry 1 }

rsvpSessionType OBJECT-TYPE  
SYNTAX SessionType  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The type of session (IP4, IP6, IP6 with flow information, etc)."  
 ::= { rsvpSessionEntry 2 }

rsvpSessionDestAddr OBJECT-TYPE  
SYNTAX OCTET STRING (SIZE(4..16))  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The destination address used by all senders in this session. This object may not be changed when the value of the RowStatus object is 'active'. "  
 ::= { rsvpSessionEntry 3 }

rsvpSessionDestAddrLength OBJECT-TYPE  
SYNTAX INTEGER(0..128)  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The CIDR prefix length of the session address, which is 32 for IP4 host and multicast addresses, and 128 for IP6 addresses. This object may not be changed when the value of the RowStatus object is 'active'. "  
 ::= { rsvpSessionEntry 4 }

rsvpSessionProtocol OBJECT-TYPE  
SYNTAX Protocol  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The IP Protocol used by this session. This object may not be changed when the value of the RowStatus object is 'active'. "  
 ::= { rsvpSessionEntry 5 }

```
::= { rsvpSessionEntry 5 }
```

```
rsvpSessionPort OBJECT-TYPE
```

```
SYNTAX      Port
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

```
"The UDP or TCP port number used as a destination port for all senders in this session. If the IP protocol in use, specified by rsvpSenderProtocol, is 50 (ESP) or 51 (AH), this represents a virtual destination port number. A value of zero indicates that the IP protocol in use does not have ports. This object may not be changed when the value of the RowStatus object is 'active'."
```

```
::= { rsvpSessionEntry 6 }
```

```
rsvpSessionSenders OBJECT-TYPE
```

```
SYNTAX      Gauge32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

```
"The number of distinct senders currently known to be part of this session."
```

```
::= { rsvpSessionEntry 7 }
```

```
rsvpSessionReceivers OBJECT-TYPE
```

```
SYNTAX      Gauge32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

```
"The number of reservations being requested of this system for this session."
```

```
::= { rsvpSessionEntry 8 }
```

```
rsvpSessionRequests OBJECT-TYPE
```

```
SYNTAX      Gauge32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

```
"The number of reservation requests this system is sending upstream for this session."
```

```
::= { rsvpSessionEntry 9 }
```

rsvpBadPackets OBJECT-TYPE

SYNTAX Gauge32  
MAX-ACCESS read-only  
STATUS current

DESCRIPTION

"This object keeps a count of the number of bad  
RSVP packets received."

::= { rsvpGenObjects 1 }

-- The RSVP Session Sender Database contains the information  
-- displayed by senders regarding their potential contribution  
-- to session data content. It is in essence a list of the  
-- valid PATH messages that the RSVP Router or Host is receiving.

rsvpSenderNewIndex OBJECT-TYPE

SYNTAX TestAndIncr  
MAX-ACCESS read-write  
STATUS current

DESCRIPTION

"This object is used to assign values to  
rsvpSenderNumber as described in 'Textual Con-  
ventions for SNMPv2'. The network manager  
reads the object, and then writes the value  
back in the SET that creates a new instance of  
rsvpSenderEntry. If the SET fails with the  
code 'inconsistentValue', then the process must  
be repeated; If the SET succeeds, then the ob-  
ject is incremented, and the new instance is  
created according to the manager's directions."

::= { rsvpGenObjects 2 }

rsvpSenderTable OBJECT-TYPE

SYNTAX SEQUENCE OF RsvpSenderEntry  
MAX-ACCESS not-accessible  
STATUS current

DESCRIPTION

"Information describing the state information  
displayed by senders in PATH messages."

::= { rsvpObjects 2 }

rsvpSenderEntry OBJECT-TYPE

SYNTAX RsvpSenderEntry  
MAX-ACCESS not-accessible  
STATUS current

## DESCRIPTION

"Information describing the state information displayed by a single sender's PATH message."

INDEX { rsvpSessionNumber, rsvpSenderNumber }  
 ::= { rsvpSenderTable 1 }

RsvpSenderEntry ::=

```
SEQUENCE {
    rsvpSenderNumber          SessionNumber,
    rsvpSenderType           SessionType,
    rsvpSenderDestAddr       OCTET STRING,
    rsvpSenderAddr           OCTET STRING,
    rsvpSenderDestAddrLength INTEGER,
    rsvpSenderAddrLength     INTEGER,
    rsvpSenderProtocol       Protocol,
    rsvpSenderDestPort       Port,
    rsvpSenderPort           Port,
    rsvpSenderFlowId         INTEGER,
    rsvpSenderHopAddr        OCTET STRING,
    rsvpSenderHopLih         Integer32,
    rsvpSenderInterface      InterfaceIndex,
    rsvpSenderTSpecRate      BitRate,
    rsvpSenderTSpecPeakRate BitRate,
    rsvpSenderTSpecBurst     BurstSize,
    rsvpSenderTSpecMinTU     MessageSize,
    rsvpSenderTSpecMaxTU     MessageSize,
    rsvpSenderInterval       RefreshInterval,
    rsvpSenderRSVPHop        TruthValue,
    rsvpSenderLastChange     TimeStamp,
    rsvpSenderPolicy          OCTET STRING,
    rsvpSenderAdspecBreak    TruthValue,
    rsvpSenderAdspecHopCount INTEGER,
    rsvpSenderAdspecPathBw   BitRate,
    rsvpSenderAdspecMinLatency Integer32,
    rsvpSenderAdspecMtu      INTEGER,
    rsvpSenderAdspecGuaranteedSvc TruthValue,
    rsvpSenderAdspecGuaranteedBreak TruthValue,
    rsvpSenderAdspecGuaranteedCtot Integer32,
    rsvpSenderAdspecGuaranteedDtot Integer32,
    rsvpSenderAdspecGuaranteedCsum Integer32,
    rsvpSenderAdspecGuaranteedDsum Integer32,
    rsvpSenderAdspecGuaranteedHopCount INTEGER,
    rsvpSenderAdspecGuaranteedPathBw BitRate,
    rsvpSenderAdspecGuaranteedMinLatency Integer32,
    rsvpSenderAdspecGuaranteedMtu      INTEGER,
    rsvpSenderAdspecCtrlLoadSvc TruthValue,
```

```

    rsvpSenderAdspecCtrlLoadBreak      TruthValue,
    rsvpSenderAdspecCtrlLoadHopCount   INTEGER,
    rsvpSenderAdspecCtrlLoadPathBw     BitRate,
    rsvpSenderAdspecCtrlLoadMinLatency Integer32,
    rsvpSenderAdspecCtrlLoadMtu        INTEGER,
    rsvpSenderStatus                    RowStatus,

    rsvpSenderTTL                       INTEGER
}

rsvpSenderNumber OBJECT-TYPE
    SYNTAX      SessionNumber
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The number of this sender. This is for SNMP
        Indexing purposes only and has no relation to
        any protocol value."
    ::= { rsvpSenderEntry 1 }

rsvpSenderType OBJECT-TYPE
    SYNTAX      SessionType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The type of session (IP4, IP6, IP6 with flow
        information, etc).".
    ::= { rsvpSenderEntry 2 }

rsvpSenderDestAddr OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(4..16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The destination address used by all senders in
        this session. This object may not be changed
        when the value of the RowStatus object is 'ac-
        tive'."
    ::= { rsvpSenderEntry 3 }

rsvpSenderAddr OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(4..16))
    MAX-ACCESS  read-create
    STATUS      current

```

## DESCRIPTION

"The source address used by this sender in this session. This object may not be changed when the value of the RowStatus object is 'active'."

::= { rsvpSenderEntry 4 }

## rsvpSenderDestAddrLength OBJECT-TYPE

SYNTAX INTEGER(0..128)

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The length of the destination address in bits. This is the CIDR Prefix Length, which for IP4 hosts and multicast addresses is 32 bits. This object may not be changed when the value of the RowStatus object is 'active'."

::= { rsvpSenderEntry 5 }

## rsvpSenderAddrLength OBJECT-TYPE

SYNTAX INTEGER(0..128)

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The length of the sender's address in bits. This is the CIDR Prefix Length, which for IP4 hosts and multicast addresses is 32 bits. This object may not be changed when the value of the RowStatus object is 'active'."

::= { rsvpSenderEntry 6 }

## rsvpSenderProtocol OBJECT-TYPE

SYNTAX Protocol

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The IP Protocol used by this session. This object may not be changed when the value of the RowStatus object is 'active'."

::= { rsvpSenderEntry 7 }

## rsvpSenderDestPort OBJECT-TYPE

SYNTAX Port

MAX-ACCESS read-create

STATUS current

## DESCRIPTION

"The UDP or TCP port number used as a destination port for all senders in this session. If the IP protocol in use, specified by rsvpSenderProtocol, is 50 (ESP) or 51 (AH), this represents a virtual destination port number. A value of zero indicates that the IP protocol in use does not have ports. This object may not be changed when the value of the RowStatus object is 'active'."

```
::= { rsvpSenderEntry 8 }
```

## rsvpSenderPort OBJECT-TYPE

```
SYNTAX      Port
MAX-ACCESS  read-create
STATUS      current
```

## DESCRIPTION

"The UDP or TCP port number used as a source port for this sender in this session. If the IP protocol in use, specified by rsvpSenderProtocol is 50 (ESP) or 51 (AH), this represents a generalized port identifier (GPI). A value of zero indicates that the IP protocol in use does not have ports. This object may not be changed when the value of the RowStatus object is 'active'."

```
::= { rsvpSenderEntry 9 }
```

## rsvpSenderFlowId OBJECT-TYPE

```
SYNTAX      INTEGER (0..16777215)
MAX-ACCESS  read-only
STATUS      current
```

## DESCRIPTION

"The flow ID that this sender is using, if this is an IPv6 session."

```
::= { rsvpSenderEntry 10 }
```

## rsvpSenderHopAddr OBJECT-TYPE

```
SYNTAX      OCTET STRING (SIZE(4..16))
MAX-ACCESS  read-create
STATUS      current
```

## DESCRIPTION

"The address used by the previous RSVP hop (which may be the original sender)."

```
::= { rsvpSenderEntry 11 }
```

```
rsvpSenderHopLih OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The Logical Interface Handle used by the previous
        RSVP hop (which may be the original sender)."
```

::= { rsvpSenderEntry 12 }

```
rsvpSenderInterface OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The ifIndex value of the interface on which
        this PATH message was most recently received."
```

::= { rsvpSenderEntry 13 }

```
rsvpSenderTSpecRate OBJECT-TYPE
    SYNTAX      BitRate
    UNITS       "bits per second"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The Average Bit Rate of the sender's data
        stream. Within a transmission burst, the arrival
        rate may be as fast as rsvpSenderTSpecPeakRate
        (if supported by the service model); however,
        averaged across two or more burst intervals,
        the rate should not exceed rsvpSenderTSpecRate."
```

Note that this is a prediction, often based on the general capability of a type of codec or particular encoding; the measured average rate may be significantly lower."

::= { rsvpSenderEntry 14 }

```
rsvpSenderTSpecPeakRate OBJECT-TYPE
    SYNTAX      BitRate
    UNITS       "bits per second"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
```

"The Peak Bit Rate of the sender's data stream. Traffic arrival is not expected to exceed this rate at any time, apart from the effects of jitter in the network. If not specified in the TSpec, this returns zero or noSuchValue."  
 ::= { rsvpSenderEntry 15 }

rsvpSenderTSpecBurst OBJECT-TYPE  
SYNTAX BurstSize  
UNITS "bytes"  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The size of the largest burst expected from the sender at a time."  
 ::= { rsvpSenderEntry 16 }

rsvpSenderTSpecMinTU OBJECT-TYPE  
SYNTAX MessageSize  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The minimum message size for this flow. The policing algorithm will treat smaller messages as though they are this size."  
 ::= { rsvpSenderEntry 17 }

rsvpSenderTSpecMaxTU OBJECT-TYPE  
SYNTAX MessageSize  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The maximum message size for this flow. The admission algorithm will reject TSpecs whose Maximum Transmission Unit, plus the interface headers, exceed the interface MTU."  
 ::= { rsvpSenderEntry 18 }

rsvpSenderInterval OBJECT-TYPE  
SYNTAX RefreshInterval  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION  
"The interval between refresh messages as ad-

vertised by the Previous Hop."  
 ::= { rsvpSenderEntry 19 }

rsvpSenderRSVPHop OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"If TRUE, the node believes that the previous IP hop is an RSVP hop. If FALSE, the node believes that the previous IP hop may not be an RSVP hop."

::= { rsvpSenderEntry 20 }

rsvpSenderLastChange OBJECT-TYPE

SYNTAX TimeStamp

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The time of the last change in this PATH message; This is either the first time it was received or the time of the most recent change in parameters."

::= { rsvpSenderEntry 21 }

rsvpSenderPolicy OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(4..65536))

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The contents of the policy object, displayed as an uninterpreted string of octets, including the object header. In the absence of such an object, this should be of zero length."

::= { rsvpSenderEntry 22 }

rsvpSenderAdspecBreak OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The global break bit general characterization parameter from the ADSPEC. If TRUE, at least one non-IS hop was detected in the path. If

```

    FALSE, no non-IS hops were detected."
 ::= { rsvpSenderEntry 23 }

```

rsvpSenderAdspecHopCount OBJECT-TYPE

SYNTAX INTEGER (0..65535)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The hop count general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set

the parameter was not present"

```
 ::= { rsvpSenderEntry 24 }
```

rsvpSenderAdspecPathBw OBJECT-TYPE

SYNTAX BitRate

UNITS "bits per second"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The path bandwidth estimate general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set

the parameter was not present"

```
 ::= { rsvpSenderEntry 25 }
```

rsvpSenderAdspecMinLatency OBJECT-TYPE

SYNTAX Integer32

UNITS "microseconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The minimum path latency general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set

the parameter was not present"

```
::= { rsvpSenderEntry 26 }
```

```
rsvpSenderAdspecMtu OBJECT-TYPE
```

```
SYNTAX      INTEGER (0..65535)
```

```
UNITS       "bytes"
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"The composed Maximum Transmission Unit general
characterization parameter from the ADSPEC. A
return of zero or noSuchValue indicates one of
the following conditions:
```

```
    the invalid bit was set
```

```
    the parameter was not present"
```

```
::= { rsvpSenderEntry 27 }
```

```
rsvpSenderAdspecGuaranteedSvc OBJECT-TYPE
```

```
SYNTAX      TruthValue
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"If TRUE, the ADSPEC contains a Guaranteed Ser-
vice fragment. If FALSE, the ADSPEC does not
contain a Guaranteed Service fragment."
```

```
::= { rsvpSenderEntry 28 }
```

```
rsvpSenderAdspecGuaranteedBreak OBJECT-TYPE
```

```
SYNTAX      TruthValue
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

```
DESCRIPTION
```

```
"If TRUE, the Guaranteed Service fragment has
its 'break' bit set, indicating that one or
more nodes along the path do not support the
guaranteed service. If FALSE, and rsvpSen-
derAdspecGuaranteedSvc is TRUE, the 'break' bit
is not set.
```

```
If rsvpSenderAdspecGuaranteedSvc is FALSE, this
returns FALSE or noSuchValue."
```

```
::= { rsvpSenderEntry 29 }
```

```
rsvpSenderAdspecGuaranteedCtot OBJECT-TYPE
```

```

SYNTAX      Integer32
UNITS       "bytes"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION

```

"If rsvpSenderAdspecGuaranteedSvc is TRUE, this is the end-to-end composed value for the guaranteed service 'C' parameter. A return of zero or noSuchValue indicates one of the following conditions:

```

    the invalid bit was set
    the parameter was not present

```

If rsvpSenderAdspecGuaranteedSvc is FALSE, this returns zero or noSuchValue."

```
 ::= { rsvpSenderEntry 30 }
```

rsvpSenderAdspecGuaranteedDtot OBJECT-TYPE

```

SYNTAX      Integer32
UNITS       "microseconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION

```

"If rsvpSenderAdspecGuaranteedSvc is TRUE, this is the end-to-end composed value for the guaranteed service 'D' parameter. A return of zero or noSuchValue indicates one of the following conditions:

```

    the invalid bit was set
    the parameter was not present

```

If rsvpSenderAdspecGuaranteedSvc is FALSE, this returns zero or noSuchValue."

```
 ::= { rsvpSenderEntry 31 }
```

rsvpSenderAdspecGuaranteedCsum OBJECT-TYPE

```

SYNTAX      Integer32
UNITS       "bytes"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION

```

"If rsvpSenderAdspecGuaranteedSvc is TRUE, this is the composed value for the guaranteed ser-

vice 'C' parameter since the last reshaping point. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
the parameter was not present

If rsvpSenderAdspecGuaranteedSvc is FALSE, this returns zero or noSuchValue."

::= { rsvpSenderEntry 32 }

rsvpSenderAdspecGuaranteedDsum OBJECT-TYPE

SYNTAX Integer32  
UNITS "microseconds"  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION

"If rsvpSenderAdspecGuaranteedSvc is TRUE, this is the composed value for the guaranteed service 'D' parameter since the last reshaping point. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
the parameter was not present

If rsvpSenderAdspecGuaranteedSvc is FALSE, this returns zero or noSuchValue."

::= { rsvpSenderEntry 33 }

rsvpSenderAdspecGuaranteedHopCount OBJECT-TYPE

SYNTAX INTEGER (0..65535)  
MAX-ACCESS read-create  
STATUS current  
DESCRIPTION

"If rsvpSenderAdspecGuaranteedSvc is TRUE, this is the service-specific override of the hop count general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
the parameter was not present

If rsvpSenderAdspecGuaranteedSvc is FALSE, this

returns zero or noSuchValue."  
 ::= { rsvpSenderEntry 34 }

rsvpSenderAdspecGuaranteedPathBw OBJECT-TYPE

SYNTAX BitRate  
 UNITS "bits per second"  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"If rsvpSenderAdspecGuaranteedSvc is TRUE, this is the service-specific override of the path bandwidth estimate general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
 the parameter was not present

If rsvpSenderAdspecGuaranteedSvc is FALSE, this returns zero or noSuchValue."  
 ::= { rsvpSenderEntry 35 }

rsvpSenderAdspecGuaranteedMinLatency OBJECT-TYPE

SYNTAX Integer32  
 UNITS "microseconds"  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"If rsvpSenderAdspecGuaranteedSvc is TRUE, this is the service-specific override of the minimum path latency general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
 the parameter was not present

If rsvpSenderAdspecGuaranteedSvc is FALSE, this returns zero or noSuchValue."  
 ::= { rsvpSenderEntry 36 }

rsvpSenderAdspecGuaranteedMtu OBJECT-TYPE

SYNTAX INTEGER (0..65535)

```

UNITS          "bytes"
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
  "If rsvpSenderAdspecGuaranteedSvc is TRUE, this
  is the service-specific override of the com-
  posed Maximum Transmission Unit general charac-
  terization parameter from the ADSPEC.  A return
  of zero or noSuchValue indicates one of the
  following conditions:

      the invalid bit was set
      the parameter was not present

  If rsvpSenderAdspecGuaranteedSvc is FALSE, this
  returns zero or noSuchValue."
 ::= { rsvpSenderEntry 37 }

```

```

rsvpSenderAdspecCtrlLoadSvc OBJECT-TYPE
SYNTAX        TruthValue
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
  "If TRUE, the ADSPEC contains a Controlled Load
  Service fragment.  If FALSE, the ADSPEC does
  not contain a Controlled Load Service frag-
  ment."
 ::= { rsvpSenderEntry 38 }

```

```

rsvpSenderAdspecCtrlLoadBreak OBJECT-TYPE
SYNTAX        TruthValue
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
  "If TRUE, the Controlled Load Service fragment
  has its 'break' bit set, indicating that one or
  more nodes along the path do not support the
  controlled load service.  If FALSE, and
  rsvpSenderAdspecCtrlLoadSvc is TRUE, the
  'break' bit is not set.

  If rsvpSenderAdspecCtrlLoadSvc is FALSE, this
  returns FALSE or noSuchValue."
 ::= { rsvpSenderEntry 39 }

```

## rsvpSenderAdspecCtrlLoadHopCount OBJECT-TYPE

SYNTAX INTEGER (0..65535)  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"If rsvpSenderAdspecCtrlLoadSvc is TRUE, this is the service-specific override of the hop count general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
 the parameter was not present

If rsvpSenderAdspecCtrlLoadSvc is FALSE, this returns zero or noSuchValue."

::= { rsvpSenderEntry 40 }

## rsvpSenderAdspecCtrlLoadPathBw OBJECT-TYPE

SYNTAX BitRate  
 UNITS "bits per second"  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"If rsvpSenderAdspecCtrlLoadSvc is TRUE, this is the service-specific override of the path bandwidth estimate general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
 the parameter was not present

If rsvpSenderAdspecCtrlLoadSvc is FALSE, this returns zero or noSuchValue."

::= { rsvpSenderEntry 41 }

## rsvpSenderAdspecCtrlLoadMinLatency OBJECT-TYPE

SYNTAX Integer32  
 UNITS "microseconds"  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION

"If rsvpSenderAdspecCtrlLoadSvc is TRUE, this

is the service-specific override of the minimum path latency general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
the parameter was not present

If rsvpSenderAdspecCtrlLoadSvc is FALSE, this returns zero or noSuchValue."

::= { rsvpSenderEntry 42 }

rsvpSenderAdspecCtrlLoadMtu OBJECT-TYPE

SYNTAX INTEGER (0..65535)

UNITS "bytes"

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"If rsvpSenderAdspecCtrlLoadSvc is TRUE, this is the service-specific override of the composed Maximum Transmission Unit general characterization parameter from the ADSPEC. A return of zero or noSuchValue indicates one of the following conditions:

the invalid bit was set  
the parameter was not present

If rsvpSenderAdspecCtrlLoadSvc is FALSE, this returns zero or noSuchValue."

::= { rsvpSenderEntry 43 }

rsvpSenderStatus OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"'active' for all active PATH messages. This object may be used to install static PATH information or delete PATH information."

::= { rsvpSenderEntry 44 }

rsvpSenderTTL OBJECT-TYPE

SYNTAX INTEGER (0..255)

```

MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The TTL value in the RSVP header that was last
    received."
 ::= { rsvpSenderEntry 45 }

```

```

rsvpSenderOutInterfaceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RsvpSenderOutInterfaceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "List of outgoing interfaces that PATH messages
        use. The ifIndex is the ifIndex value of the
        egress interface."
    ::= { rsvpObjects 3 }

```

```

rsvpSenderOutInterfaceEntry OBJECT-TYPE
    SYNTAX      RsvpSenderOutInterfaceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "List of outgoing interfaces that a particular
        PATH message has."
    INDEX { rsvpSessionNumber, rsvpSenderNumber, ifIndex }
    ::= { rsvpSenderOutInterfaceTable 1 }

```

```

RsvpSenderOutInterfaceEntry ::=
    SEQUENCE {
        rsvpSenderOutInterfaceStatus          RowStatus
    }

```

```

rsvpSenderOutInterfaceStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "'active' for all active PATH messages."
    ::= { rsvpSenderOutInterfaceEntry 1 }

```

```

--      The RSVP Reservation Requests Received Table contains the
--      information displayed by receivers regarding their needs with
--      respect to sessions and senders. It is in essence a list of the
--      valid RESV messages that the RSVP Router or Host is receiving.

```

```

rsvpResvNewIndex OBJECT-TYPE
    SYNTAX      TestAndIncr
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object is used to assign values to
        rsvpResvNumber as described in 'Textual Conven-
        tions for SNMPv2'. The network manager reads
        the object, and then writes the value back in
        the SET that creates a new instance of
        rsvpResvEntry. If the SET fails with the code
        'inconsistentValue', then the process must be
        repeated; If the SET succeeds, then the object
        is incremented, and the new instance is created
        according to the manager's directions."
    ::= { rsvpGenObjects 3 }

```

```

rsvpResvTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RsvpResvEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information describing the state information
        displayed by receivers in RESV messages."
    ::= { rsvpObjects 4 }

```

```

rsvpResvEntry OBJECT-TYPE
    SYNTAX      RsvpResvEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Information describing the state information
        displayed by a single receiver's RESV message
        concerning a single sender."
    INDEX { rsvpSessionNumber, rsvpResvNumber }
    ::= { rsvpResvTable 1 }

```

```

RsvpResvEntry ::=
    SEQUENCE {
        rsvpResvNumber          SessionNumber,
        rsvpResvType            SessionType,
        rsvpResvDestAddr        OCTET STRING,
        rsvpResvSenderAddr      OCTET STRING,
        rsvpResvDestAddrLength  INTEGER,

```

```

    rsvpResvSenderAddrLength      INTEGER,
    rsvpResvProtocol              Protocol,
    rsvpResvDestPort              Port,
    rsvpResvPort                  Port,
    rsvpResvHopAddr               OCTET STRING,
    rsvpResvHopLih                Integer32,
    rsvpResvInterface             InterfaceIndex,
    rsvpResvService                QosService,
    rsvpResvTSpecRate             BitRate,
    rsvpResvTSpecPeakRate         BitRate,
    rsvpResvTSpecBurst            BurstSize,
    rsvpResvTSpecMinTU            MessageSize,
    rsvpResvTSpecMaxTU            MessageSize,
    rsvpResvRSpecRate             BitRate,
    rsvpResvRSpecSlack            Integer32,
    rsvpResvInterval              RefreshInterval,
    rsvpResvScope                 OCTET STRING,
    rsvpResvShared                TruthValue,
    rsvpResvExplicit              TruthValue,
    rsvpResvRSVPHop               TruthValue,
    rsvpResvLastChange            TimeStamp,
    rsvpResvPolicy                 OCTET STRING,
    rsvpResvStatus                RowStatus,
    rsvpResvTTL                   INTEGER,
    rsvpResvFlowId                 INTEGER
}

```

```

rsvpResvNumber OBJECT-TYPE
    SYNTAX          SessionNumber
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "The number of this reservation request.  This
         is for SNMP Indexing purposes only and has no
         relation to any protocol value."
    ::= { rsvpResvEntry 1 }

```

```

rsvpResvType OBJECT-TYPE
    SYNTAX          SessionType
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "The type of session (IP4, IP6, IP6 with flow
         information, etc).".
    ::= { rsvpResvEntry 2 }

```

```
rsvpResvDestAddr OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(4..16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The destination address used by all senders in
        this session.  This object may not be changed
        when the value of the RowStatus object is 'ac-
        tive'."
    ::= { rsvpResvEntry 3 }

rsvpResvSenderAddr OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(4..16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The source address of the sender selected by
        this reservation.  The value of all zeroes in-
        dicates 'all senders'.  This object may not be
        changed when the value of the RowStatus object
        is 'active'."
    ::= { rsvpResvEntry 4 }

rsvpResvDestAddrLength OBJECT-TYPE
    SYNTAX      INTEGER(0..128)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The length of the destination address in bits.
        This is the CIDR Prefix Length, which for IP4
        hosts and multicast addresses is 32 bits.  This
        object may not be changed when the value of the
        RowStatus object is 'active'."
    ::= { rsvpResvEntry 5 }

rsvpResvSenderAddrLength OBJECT-TYPE
    SYNTAX      INTEGER(0..128)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The length of the sender's address in bits.
        This is the CIDR Prefix Length, which for IP4
        hosts and multicast addresses is 32 bits.  This
        object may not be changed when the value of the
        RowStatus object is 'active'."
```

```
::= { rsvpResvEntry 6 }
```

```
rsvpResvProtocol OBJECT-TYPE
```

```
SYNTAX      Protocol
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

```
"The IP Protocol used by this session. This
object may not be changed when the value of the
RowStatus object is 'active'."
```

```
::= { rsvpResvEntry 7 }
```

```
rsvpResvDestPort OBJECT-TYPE
```

```
SYNTAX      Port
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

```
"The UDP or TCP port number used as a destina-
tion port for all senders in this session. If
the IP protocol in use, specified by
rsvpResvProtocol, is 50 (ESP) or 51 (AH), this
represents a virtual destination port number.
A value of zero indicates that the IP protocol
in use does not have ports. This object may
not be changed when the value of the RowStatus
object is 'active'."
```

```
::= { rsvpResvEntry 8 }
```

```
rsvpResvPort OBJECT-TYPE
```

```
SYNTAX      Port
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

```
"The UDP or TCP port number used as a source
port for this sender in this session. If the
IP protocol in use, specified by rsvpResvProto-
col is 50 (ESP) or 51 (AH), this represents a
generalized port identifier (GPI). A value of
zero indicates that the IP protocol in use does
not have ports. This object may not be changed
when the value of the RowStatus object is 'ac-
tive'."
```

```
::= { rsvpResvEntry 9 }
```

```
rsvpResvHopAddr OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(4..16))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The address used by the next RSVP hop (which
         may be the ultimate receiver)."
```

```
 ::= { rsvpResvEntry 10 }
```

  

```
rsvpResvHopLih OBJECT-TYPE
    SYNTAX      Integer32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The Logical Interface Handle received from the
         previous RSVP hop (which may be the ultimate
         receiver)."
```

```
 ::= { rsvpResvEntry 11 }
```

  

```
rsvpResvInterface OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The ifIndex value of the interface on which
         this RESV message was most recently received."
```

```
 ::= { rsvpResvEntry 12 }
```

  

```
rsvpResvService OBJECT-TYPE
    SYNTAX      QoSService
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The QoS Service classification requested by
         the receiver."
```

```
 ::= { rsvpResvEntry 13 }
```

  

```
rsvpResvTSpecRate OBJECT-TYPE
    SYNTAX      BitRate
    UNITS       "bits per second"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The Average Bit Rate of the sender's data
```

stream. Within a transmission burst, the arrival rate may be as fast as rsvpResvTSpecPeakRate (if supported by the service model); however, averaged across two or more burst intervals, the rate should not exceed rsvpResvTSpecRate.

Note that this is a prediction, often based on the general capability of a type of codec or particular encoding; the measured average rate may be significantly lower."

```
::= { rsvpResvEntry 14 }
```

rsvpResvTSpecPeakRate OBJECT-TYPE

```
SYNTAX      BitRate
UNITS       "bits per second"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"The Peak Bit Rate of the sender's data stream. Traffic arrival is not expected to exceed this rate at any time, apart from the effects of jitter in the network. If not specified in the TSpec, this returns zero or noSuchValue."

```
::= { rsvpResvEntry 15 }
```

rsvpResvTSpecBurst OBJECT-TYPE

```
SYNTAX      BurstSize
UNITS       "bytes"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"The size of the largest burst expected from the sender at a time.

If this is less than the sender's advertised burst size, the receiver is asking the network to provide flow pacing beyond what would be provided under normal circumstances. Such pacing is at the network's option."

```
::= { rsvpResvEntry 16 }
```

rsvpResvTSpecMinTU OBJECT-TYPE

```
SYNTAX      MessageSize
MAX-ACCESS  read-create
```

```
STATUS      current
DESCRIPTION
    "The minimum message size for this flow. The
    policing algorithm will treat smaller messages
    as though they are this size."
 ::= { rsvpResvEntry 17 }
```

rsvpResvTSpecMaxTU OBJECT-TYPE

```
SYNTAX      MessageSize
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The maximum message size for this flow. The
    admission algorithm will reject TSpecs whose
    Maximum Transmission Unit, plus the interface
    headers, exceed the interface MTU."
 ::= { rsvpResvEntry 18 }
```

rsvpResvRSpecRate OBJECT-TYPE

```
SYNTAX      BitRate
UNITS       "bits per second"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "If the requested service is Guaranteed, as
    specified by rsvpResvService, this is the
    clearing rate that is being requested. Other-
    wise, it is zero, or the agent may return
    noSuchValue."
 ::= { rsvpResvEntry 19 }
```

rsvpResvRSpecSlack OBJECT-TYPE

```
SYNTAX      Integer32
UNITS       "microseconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "If the requested service is Guaranteed, as
    specified by rsvpResvService, this is the delay
    slack. Otherwise, it is zero, or the agent may
    return noSuchValue."
 ::= { rsvpResvEntry 20 }
```

rsvpResvInterval OBJECT-TYPE

```
SYNTAX      RefreshInterval
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The interval between refresh messages as advertised by the Next Hop."
 ::= { rsvpResvEntry 21 }
```

rsvpResvScope OBJECT-TYPE

```
SYNTAX      OCTET STRING (SIZE(0..65536))
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"The contents of the scope object, displayed as an uninterpreted string of octets, including the object header. In the absence of such an object, this should be of zero length.

If the length is non-zero, this contains a series of IP4 or IP6 addresses."

```
 ::= { rsvpResvEntry 22 }
```

rsvpResvShared OBJECT-TYPE

```
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"If TRUE, a reservation shared among senders is requested. If FALSE, a reservation specific to this sender is requested."

```
 ::= { rsvpResvEntry 23 }
```

rsvpResvExplicit OBJECT-TYPE

```
SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
```

"If TRUE, individual senders are listed using Filter Specifications. If FALSE, all senders are implicitly selected. The Scope Object will contain a list of senders that need to receive this reservation request for the purpose of routing the RESV message."

```
 ::= { rsvpResvEntry 24 }
```

```
rsvpResvRSVPHop OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "If TRUE, the node believes that the previous
         IP hop is an RSVP hop.  If FALSE, the node be-
         lieves that the previous IP hop may not be an
         RSVP hop."
    ::= { rsvpResvEntry 25 }

rsvpResvLastChange OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time of the last change in this reserva-
         tion request; This is either the first time it
         was received or the time of the most recent
         change in parameters."
    ::= { rsvpResvEntry 26 }

rsvpResvPolicy OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(0..65536))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The contents of the policy object, displayed
         as an uninterpreted string of octets, including
         the object header.  In the absence of such an
         object, this should be of zero length."
    ::= { rsvpResvEntry 27 }

rsvpResvStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "'active' for all active RESV messages.  This
         object may be used to install static RESV in-
         formation or delete RESV information."
    ::= { rsvpResvEntry 28 }

rsvpResvTTL OBJECT-TYPE
```

```

SYNTAX      INTEGER (0..255)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The TTL value in the RSVP header that was last
    received."
 ::= { rsvpResvEntry 29 }

```

```

rsvpResvFlowId OBJECT-TYPE
SYNTAX      INTEGER (0..16777215)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The flow ID that this receiver is using, if
    this is an IPv6 session."
 ::= { rsvpResvEntry 30 }

```

```

--      The RSVP Reservation Requests Forwarded Table contains the
--      information displayed by receivers regarding their needs with
--      respect to sessions and senders. It is in essence a list of the
--      valid RESV messages that the RSVP Router or Host is sending
--      to its upstream neighbors.

```

```

rsvpResvFwdNewIndex OBJECT-TYPE
SYNTAX      TestAndIncr
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "This object is used to assign values to
    rsvpResvFwdNumber as described in 'Textual Con-
    vention for SNMPv2'. The network manager
    reads the object, and then writes the value
    back in the SET that creates a new instance of
    rsvpResvFwdEntry. If the SET fails with the
    code 'inconsistentValue', then the process must
    be repeated; If the SET succeeds, then the ob-
    ject is incremented, and the new instance is
    created according to the manager's directions."
 ::= { rsvpGenObjects 4 }

```

```

rsvpResvFwdTable OBJECT-TYPE
SYNTAX      SEQUENCE OF RsvpResvFwdEntry
MAX-ACCESS  not-accessible
STATUS      current

```

## DESCRIPTION

"Information describing the state information displayed upstream in RESV messages."

::= { rsvpObjects 5 }

## rsvpResvFwdEntry OBJECT-TYPE

SYNTAX RsvpResvFwdEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"Information describing the state information displayed upstream in an RESV message concerning a single sender."

INDEX { rsvpSessionNumber, rsvpResvFwdNumber }

::= { rsvpResvFwdTable 1 }

## RsvpResvFwdEntry ::=

## SEQUENCE {

rsvpResvFwdNumber	SessionNumber,
rsvpResvFwdType	SessionType,
rsvpResvFwdDestAddr	OCTET STRING,
rsvpResvFwdSenderAddr	OCTET STRING,
rsvpResvFwdDestAddrLength	INTEGER,
rsvpResvFwdSenderAddrLength	INTEGER,
rsvpResvFwdProtocol	Protocol,
rsvpResvFwdDestPort	Port,
rsvpResvFwdPort	Port,
rsvpResvFwdHopAddr	OCTET STRING,
rsvpResvFwdHopLih	Integer32,
rsvpResvFwdInterface	InterfaceIndex,
rsvpResvFwdService	QosService,
rsvpResvFwdTSpecRate	BitRate,
rsvpResvFwdTSpecPeakRate	BitRate,
rsvpResvFwdTSpecBurst	BurstSize,
rsvpResvFwdTSpecMinTU	MessageSize,
rsvpResvFwdTSpecMaxTU	MessageSize,
rsvpResvFwdRSpecRate	BitRate,
rsvpResvFwdRSpecSlack	Integer32,
rsvpResvFwdInterval	RefreshInterval,
rsvpResvFwdScope	OCTET STRING,
rsvpResvFwdShared	TruthValue,
rsvpResvFwdExplicit	TruthValue,
rsvpResvFwdRSVPHop	TruthValue,
rsvpResvFwdLastChange	TimeStamp,
rsvpResvFwdPolicy	OCTET STRING,
rsvpResvFwdStatus	RowStatus,

```

    rsvpResvFwdTTL                INTEGER,
    rsvpResvFwdFlowId             INTEGER
}

```

```

rsvpResvFwdNumber OBJECT-TYPE
    SYNTAX          SessionNumber
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "The number of this reservation request.  This
         is for SNMP Indexing purposes only and has no
         relation to any protocol value."
    ::= { rsvpResvFwdEntry 1 }

```

```

rsvpResvFwdType OBJECT-TYPE
    SYNTAX          SessionType
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The type of session (IP4, IP6, IP6 with flow
         information, etc).".
    ::= { rsvpResvFwdEntry 2 }

```

```

rsvpResvFwdDestAddr OBJECT-TYPE
    SYNTAX          OCTET STRING (SIZE(4..16))
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The destination address used by all senders in
         this session.  This object may not be changed
         when the value of the RowStatus object is 'ac-
         tive'."
    ::= { rsvpResvFwdEntry 3 }

```

```

rsvpResvFwdSenderAddr OBJECT-TYPE
    SYNTAX          OCTET STRING (SIZE(4..16))
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The source address of the sender selected by
         this reservation.  The value of all zeroes in-
         dicates 'all senders'.  This object may not be
         changed when the value of the RowStatus object
         is 'active'."

```

```
::= { rsvpResvFwdEntry 4 }
```

```
rsvpResvFwdDestAddrLength OBJECT-TYPE
```

```
SYNTAX          INTEGER(0..128)
```

```
MAX-ACCESS     read-only
```

```
STATUS         current
```

```
DESCRIPTION
```

```
"The length of the destination address in bits.
This is the CIDR Prefix Length, which for IP4
hosts and multicast addresses is 32 bits. This
object may not be changed when the value of the
RowStatus object is 'active'."
```

```
::= { rsvpResvFwdEntry 5 }
```

```
rsvpResvFwdSenderAddrLength OBJECT-TYPE
```

```
SYNTAX          INTEGER(0..128)
```

```
MAX-ACCESS     read-only
```

```
STATUS         current
```

```
DESCRIPTION
```

```
"The length of the sender's address in bits.
This is the CIDR Prefix Length, which for IP4
hosts and multicast addresses is 32 bits. This
object may not be changed when the value of the
RowStatus object is 'active'."
```

```
::= { rsvpResvFwdEntry 6 }
```

```
rsvpResvFwdProtocol OBJECT-TYPE
```

```
SYNTAX          Protocol
```

```
MAX-ACCESS     read-only
```

```
STATUS         current
```

```
DESCRIPTION
```

```
"The IP Protocol used by a session. for secure
sessions, this indicates IP Security. This ob-
ject may not be changed when the value of the
RowStatus object is 'active'."
```

```
::= { rsvpResvFwdEntry 7 }
```

```
rsvpResvFwdDestPort OBJECT-TYPE
```

```
SYNTAX          Port
```

```
MAX-ACCESS     read-only
```

```
STATUS         current
```

```
DESCRIPTION
```

```
"The UDP or TCP port number used as a destina-
tion port for all senders in this session. If
```

the IP protocol in use, specified by rsvpResvFwdProtocol, is 50 (ESP) or 51 (AH), this represents a virtual destination port number. A value of zero indicates that the IP protocol in use does not have ports. This object may not be changed when the value of the RowStatus object is 'active'."

```
::= { rsvpResvFwdEntry 8 }
```

rsvpResvFwdPort OBJECT-TYPE

```
SYNTAX      Port
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"The UDP or TCP port number used as a source port for this sender in this session. If the IP protocol in use, specified by rsvpResvFwdProtocol is 50 (ESP) or 51 (AH), this represents a generalized port identifier (GPI). A value of zero indicates that the IP protocol in use does not have ports. This object may not be changed when the value of the RowStatus object is 'active'."

```
::= { rsvpResvFwdEntry 9 }
```

rsvpResvFwdHopAddr OBJECT-TYPE

```
SYNTAX      OCTET STRING (SIZE(4..16))
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"The address of the (previous) RSVP that will receive this message."

```
::= { rsvpResvFwdEntry 10 }
```

rsvpResvFwdHopLih OBJECT-TYPE

```
SYNTAX      Integer32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"The Logical Interface Handle sent to the (previous) RSVP that will receive this message."

```
::= { rsvpResvFwdEntry 11 }
```

rsvpResvFwdInterface OBJECT-TYPE

```

SYNTAX      InterfaceIndex
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The ifIndex value of the interface on which
    this RESV message was most recently sent."
 ::= { rsvpResvFwdEntry 12 }

```

rsvpResvFwdService OBJECT-TYPE

```

SYNTAX      QoSService
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The QoS Service classification requested."
 ::= { rsvpResvFwdEntry 13 }

```

rsvpResvFwdTSpecRate OBJECT-TYPE

```

SYNTAX      BitRate
UNITS       "bits per second"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The Average Bit Rate of the sender's data
    stream. Within a transmission burst, the ar-
    rival rate may be as fast as rsvpResvFwdTSpec-
    PeakRate (if supported by the service model);
    however, averaged across two or more burst in-
    tervals, the rate should not exceed
    rsvpResvFwdTSpecRate.

```

Note that this is a prediction, often based on the general capability of a type of codec or particular encoding; the measured average rate may be significantly lower."

```

 ::= { rsvpResvFwdEntry 14 }

```

rsvpResvFwdTSpecPeakRate OBJECT-TYPE

```

SYNTAX      BitRate
UNITS       "bits per second"
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The Peak Bit Rate of the sender's data stream
    Traffic arrival is not expected to exceed this
    rate at any time, apart from the effects of

```

jitter in the network. If not specified in the TSpec, this returns zero or noSuchValue."  
 ::= { rsvpResvFwdEntry 15 }

rsvpResvFwdTSpecBurst OBJECT-TYPE

SYNTAX BurstSize  
 UNITS "bytes"  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION

"The size of the largest burst expected from the sender at a time.

If this is less than the sender's advertised burst size, the receiver is asking the network to provide flow pacing beyond what would be provided under normal circumstances. Such pacing is at the network's option."

::= { rsvpResvFwdEntry 16 }

rsvpResvFwdTSpecMinTU OBJECT-TYPE

SYNTAX MessageSize  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION

"The minimum message size for this flow. The policing algorithm will treat smaller messages as though they are this size."

::= { rsvpResvFwdEntry 17 }

rsvpResvFwdTSpecMaxTU OBJECT-TYPE

SYNTAX MessageSize  
 MAX-ACCESS read-only  
 STATUS current  
 DESCRIPTION

"The maximum message size for this flow. The admission algorithm will reject TSpecs whose Maximum Transmission Unit, plus the interface headers, exceed the interface MTU."

::= { rsvpResvFwdEntry 18 }

rsvpResvFwdRSpecRate OBJECT-TYPE

SYNTAX BitRate  
 UNITS "bytes per second"

```

MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "If the requested service is Guaranteed, as
    specified by rsvpResvService, this is the
    clearing rate that is being requested.  Other-
    wise, it is zero, or the agent may return
    noSuchValue."
 ::= { rsvpResvFwdEntry 19 }

```

```

rsvpResvFwdRSpecSlack OBJECT-TYPE
SYNTAX        Integer32
UNITS         "microseconds"
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "If the requested service is Guaranteed, as
    specified by rsvpResvService, this is the delay
    slack.  Otherwise, it is zero, or the agent may
    return noSuchValue."
 ::= { rsvpResvFwdEntry 20 }

```

```

rsvpResvFwdInterval OBJECT-TYPE
SYNTAX        RefreshInterval
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The interval between refresh messages adver-
    tised to the Previous Hop."
 ::= { rsvpResvFwdEntry 21 }

```

```

rsvpResvFwdScope OBJECT-TYPE
SYNTAX        OCTET STRING (SIZE(0..65536))
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The contents of the scope object, displayed as
    an uninterpreted string of octets, including
    the object header.  In the absence of such an
    object, this should be of zero length."
 ::= { rsvpResvFwdEntry 22 }

```

```

rsvpResvFwdShared OBJECT-TYPE
SYNTAX        TruthValue

```

```
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "If TRUE, a reservation shared among senders is
    requested.  If FALSE, a reservation specific to
    this sender is requested."
 ::= { rsvpResvFwdEntry 23 }
```

```
rsvpResvFwdExplicit OBJECT-TYPE
SYNTAX        TruthValue
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "If TRUE, individual senders are listed using
    Filter Specifications.  If FALSE, all senders
    are implicitly selected.  The Scope Object will
    contain a list of senders that need to receive
    this reservation request for the purpose of
    routing the RESV message."
 ::= { rsvpResvFwdEntry 24 }
```

```
rsvpResvFwdRSVPHop OBJECT-TYPE
SYNTAX        TruthValue
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "If TRUE, the node believes that the next IP
    hop is an RSVP hop.  If FALSE, the node be-
    lieves that the next IP hop may not be an RSVP
    hop."
 ::= { rsvpResvFwdEntry 25 }
```

```
rsvpResvFwdLastChange OBJECT-TYPE
SYNTAX        TimeStamp
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The time of the last change in this request;
    This is either the first time it was sent or
    the time of the most recent change in parame-
    ters."
 ::= { rsvpResvFwdEntry 26 }
```

```
rsvpResvFwdPolicy OBJECT-TYPE
```

```

SYNTAX      OCTET STRING (SIZE(0..65536))
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The contents of the policy object, displayed
    as an uninterpreted string of octets, including
    the object header. In the absence of such an
    object, this should be of zero length."
 ::= { rsvpResvFwdEntry 27 }

```

```

rsvpResvFwdStatus OBJECT-TYPE
SYNTAX      RowStatus
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
    "'active' for all active RESV messages. This
    object may be used to delete RESV information."
 ::= { rsvpResvFwdEntry 28 }

```

```

rsvpResvFwdTTL OBJECT-TYPE
SYNTAX      INTEGER (0..255)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The TTL value in the RSVP header that was last
    received."
 ::= { rsvpResvFwdEntry 29 }

```

```

rsvpResvFwdFlowId OBJECT-TYPE
SYNTAX      INTEGER (0..16777215)
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The flow ID that this receiver is using, if
    this is an IPv6 session."
 ::= { rsvpResvFwdEntry 30 }

```

```

-- The RSVP Interface Attributes Database contains the
-- RSVP-specific information for an interface. Information
-- that is shared with other reservation procedures such
-- as ST-II is in the Integrated Interface Attributes
-- Database.

```

```

rsvpIfTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RsvpIfEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The RSVP-specific attributes of the system's
        interfaces."
    ::= { rsvpObjects 6 }

```

```

rsvpIfEntry OBJECT-TYPE
    SYNTAX      RsvpIfEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The RSVP-specific attributes of the a given
        interface."
    INDEX { ifIndex }
    ::= { rsvpIfTable 1 }

```

```

RsvpIfEntry ::=
    SEQUENCE {
        rsvpIfUdpNbrs          Gauge32,
        rsvpIfIpNbrs          Gauge32,
        rsvpIfNbrs            Gauge32,
        rsvpIfEnabled         TruthValue,
        rsvpIfUdpRequired     TruthValue,
        rsvpIfRefreshBlockadeMultiple  INTEGER,
        rsvpIfRefreshMultiple  INTEGER,
        rsvpIfTTL             INTEGER,
        rsvpIfRefreshInterval TimeInterval,
        rsvpIfRouteDelay      TimeInterval,
        rsvpIfStatus          RowStatus
    }

```

```

rsvpIfUdpNbrs OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of neighbors perceived to be using
        only the RSVP UDP Encapsulation."
    ::= { rsvpIfEntry 1 }

```

```

rsvpIfIpNbrs OBJECT-TYPE
    SYNTAX      Gauge32

```

```

MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The number of neighbors perceived to be using
    only the RSVP IP Encapsulation."
 ::= { rsvpIfEntry 2 }

```

```

rsvpIfNbrs OBJECT-TYPE
SYNTAX        Gauge32
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The number of neighbors currently perceived;
    this will exceed rsvpIfIpNbrs + rsvpIfUdpNbrs
    by the number of neighbors using both encapsu-
    lations."
 ::= { rsvpIfEntry 3 }

```

```

rsvpIfRefreshBlockadeMultiple OBJECT-TYPE
SYNTAX        INTEGER (1..65536)
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
    "The value of the RSVP value 'Kb', which is the
    minimum number of refresh intervals that
    blockade state will last once entered."
DEFVAL        { 4 }
 ::= { rsvpIfEntry 4 }

```

```

rsvpIfRefreshMultiple OBJECT-TYPE
SYNTAX        INTEGER (1..65536)
MAX-ACCESS    read-create
STATUS        current
DESCRIPTION
    "The value of the RSVP value 'K', which is the
    number of refresh intervals which must elapse
    (minimum) before a PATH or RESV message which
    is not being refreshed will be aged out."
DEFVAL        { 3 }
 ::= { rsvpIfEntry 5 }

```

```

rsvpIfTTL OBJECT-TYPE
SYNTAX        INTEGER (0..255)
MAX-ACCESS    read-create

```

```

STATUS      current
DESCRIPTION
    "The value of SEND_TTL used on this interface
    for messages this node originates.  If set to
    zero, the node determines the TTL via other
    means."
DEFVAL { 0 } -- which is to say, no override
 ::= { rsvpIfEntry 6 }

```

rsvpIfRefreshInterval OBJECT-TYPE

```

SYNTAX      TimeInterval
UNITS       "milliseconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The value of the RSVP value 'R', which is the
    minimum period between refresh transmissions of
    a given PATH or RESV message on an interface."
DEFVAL      { 3000 } -- 30 seconds
 ::= { rsvpIfEntry 7 }

```

rsvpIfRouteDelay OBJECT-TYPE

```

SYNTAX      TimeInterval
UNITS       "hundredths of a second"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "The approximate period from the time a route
    is changed to the time a resulting message ap-
    pears on the interface."
DEFVAL      { 200 } -- 2 seconds
 ::= { rsvpIfEntry 8 }

```

rsvpIfEnabled OBJECT-TYPE

```

SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "If TRUE, RSVP is enabled on this Interface.
    If FALSE, RSVP is not enabled on this inter-
    face."
 ::= { rsvpIfEntry 9 }

```

rsvpIfUdpRequired OBJECT-TYPE

```

SYNTAX      TruthValue
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION
    "If TRUE, manual configuration forces the use
    of UDP encapsulation on the interface. If
    FALSE, UDP encapsulation is only used if rsvpI-
    fUdpNbrs is not zero."

```

```
 ::= { rsvpIfEntry 10 }
```

```
rsvpIfStatus OBJECT-TYPE
```

```

SYNTAX      RowStatus
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION

```

```
    "'active' on interfaces that are configured for
    RSVP."
```

```
 ::= { rsvpIfEntry 11 }
```

```

--      The RSVP Neighbor Database lists the neighbors the RSVP
--      process currently is receiving messages from.

```

```
rsvpNbrTable OBJECT-TYPE
```

```

SYNTAX      SEQUENCE OF RsvpNbrEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION

```

```
    "Information describing the Neighbors of an
    RSVP system."
```

```
 ::= { rsvpObjects 7 }
```

```
rsvpNbrEntry OBJECT-TYPE
```

```

SYNTAX      RsvpNbrEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION

```

```
    "Information describing a single RSVP Neigh-
    bor."
```

```
INDEX { ifIndex, rsvpNbrAddress }
```

```
 ::= { rsvpNbrTable 1 }
```

```

RsvpNbrEntry ::=
    SEQUENCE {

```

```

rsvpNbrAddress      OCTET STRING,
rsvpNbrProtocol    RsvpEncapsulation,
rsvpNbrStatus      RowStatus
}

rsvpNbrAddress OBJECT-TYPE
    SYNTAX          OCTET STRING (SIZE(4..16))
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "The IP4 or IP6 Address used by this neighbor.
        This object may not be changed when the value
        of the RowStatus object is 'active'."
    ::= { rsvpNbrEntry 1 }

rsvpNbrProtocol OBJECT-TYPE
    SYNTAX          RsvpEncapsulation
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "The encapsulation being used by this neigh-
        bor."
    ::= { rsvpNbrEntry 2 }

rsvpNbrStatus OBJECT-TYPE
    SYNTAX          RowStatus
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "'active' for all neighbors. This object may
        be used to configure neighbors. In the pres-
        ence of configured neighbors, the implementa-
        tion may (but is not required to) limit the set
        of valid neighbors to those configured."
    ::= { rsvpNbrEntry 3 }

--
--      Notifications used to signal events
--

rsvpNotifications OBJECT IDENTIFIER
    ::= { rsvpNotificationsPrefix 0 }

newFlow NOTIFICATION-TYPE

```

```

OBJECTS {
    intSrvFlowStatus, rsvpSessionDestAddr,
    rsvpResvFwdStatus, rsvpResvStatus, rsvpSenderStatus
}

```

```
STATUS current
```

```
DESCRIPTION
```

```

"The newFlow trap indicates that the originat-
ing system has installed a new flow in its
classifier, or (when reservation authorization
is in view) is prepared to install such a flow
in the classifier and is requesting authoriza-
tion. The objects included with the Notifica-
tion may be used to read further information
using the Integrated Services and RSVP MIBs.
Authorization or non-authorization may be
enacted by a write to the variable intSrvFlowS-
tatus."

```

```
::= { rsvpNotifications 1 }
```

```
lostFlow NOTIFICATION-TYPE
```

```

OBJECTS {
    intSrvFlowStatus, rsvpSessionDestAddr,
    rsvpResvFwdStatus, rsvpResvStatus, rsvpSenderStatus
}

```

```
STATUS current
```

```
DESCRIPTION
```

```

"The lostFlow trap indicates that the originat-
ing system has removed a flow from its classif-
ier."

```

```
::= { rsvpNotifications 2 }
```

```
-- conformance information
```

```

rsvpGroups      OBJECT IDENTIFIER ::= { rsvpConformance 1 }
rsvpCompliances OBJECT IDENTIFIER ::= { rsvpConformance 2 }

```

```
-- compliance statements
```

```
rsvpCompliance MODULE-COMPLIANCE
```

```
STATUS current
```

```
DESCRIPTION
```

```

"The compliance statement. Note that the im-
plementation of this module requires implemen-
tation of the Integrated Services MIB as well."

```

```
MODULE -- this module
MANDATORY-GROUPS {
    rsvpSessionGroup, rsvpSenderGroup, rsvpResvGroup,
    rsvpIfGroup, rsvpNbrGroup
}
```

```
GROUP rsvpResvFwdGroup
```

```
DESCRIPTION
```

```
"The Reservation Requests table is appropriate
in implementations that store upstream reserva-
tion messages, but not appropriate in implemen-
tations which calculate them on each transmis-
sion."
```

```
GROUP rsvpNotificationGroup
```

```
DESCRIPTION
```

```
"The notifications in this module may be used to
advise a network management station of changes in
flow status, and are required when this use is in
view."
```

```
OBJECT rsvpSessionRequests
```

```
MIN-ACCESS not-accessible
```

```
DESCRIPTION
```

```
"This object is optional."
```

```
OBJECT rsvpSenderType
```

```
MIN-ACCESS read-only
```

```
DESCRIPTION
```

```
"read-create access is not required. This may be
read-only."
```

```
OBJECT rsvpSenderDestAddr
```

```
MIN-ACCESS read-only
```

```
DESCRIPTION
```

```
"read-create access is not required. This may be
read-only."
```

```
OBJECT rsvpSenderAddr
```

```
MIN-ACCESS read-only
```

```
DESCRIPTION
```

```
"read-create access is not required. This may be
read-only."
```

```
OBJECT rsvpSenderDestAddrLength
```

```
MIN-ACCESS read-only
```

```
DESCRIPTION
```

```
"read-create access is not required. This may be
```

read-only."

OBJECT            rsvpSenderAddrLength  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderProtocol  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderDestPort  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderPort  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderHopAddr  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderHopLih  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderInterface  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderTSpecRate  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be

read-only."

OBJECT            rsvpSenderTSpecPeakRate  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderTSpecBurst  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderTSpecMinTU  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderTSpecMaxTU  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderInterval  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderRSVPHop  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderPolicy  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderAdspecBreak  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be

read-only."

OBJECT            rsvpSenderAdspecHopCount  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderAdspecPathBw  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderAdspecMinLatency  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderAdspecMtu  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be  
read-only."

OBJECT            rsvpSenderAdspecGuaranteedSvc  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedBreak  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedCtot  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedDtot  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not

support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedCsum  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedDsum  
MIN-ACCESS read-only  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedHopCount  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedPathBw  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedMinLatency  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecGuaranteedMtu  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Guaranteed Service."

OBJECT            rsvpSenderAdspecCtrlLoadSvc  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not  
support Controlled Load."

OBJECT            rsvpSenderAdspecCtrlLoadBreak  
MIN-ACCESS not-accessible  
DESCRIPTION  
"This may be not-accessible if the system does not

support Controlled Load."

OBJECT            rsvpSenderAdspecCtrlLoadHopCount  
MIN-ACCESS not-accessible  
DESCRIPTION  
  "This may be not-accessible if the system does not  
  support Controlled Load."

OBJECT            rsvpSenderAdspecCtrlLoadPathBw  
MIN-ACCESS not-accessible  
DESCRIPTION  
  "This may be not-accessible if the system does not  
  support Controlled Load."

OBJECT            rsvpSenderAdspecCtrlLoadMinLatency  
MIN-ACCESS not-accessible  
DESCRIPTION  
  "This may be not-accessible if the system does not  
  support Controlled Load."

OBJECT            rsvpSenderAdspecCtrlLoadMtu  
MIN-ACCESS not-accessible  
DESCRIPTION  
  "This may be not-accessible if the system does not  
  support Controlled Load."

OBJECT            rsvpSenderStatus  
MIN-ACCESS read-only  
DESCRIPTION  
  "read-create access is not required. This may be  
  read-only."

OBJECT            rsvpSenderFlowId  
MIN-ACCESS not-accessible  
DESCRIPTION  
  "This object is needed only in a system that imple-  
  ments IPv6."

OBJECT            rsvpResvType  
MIN-ACCESS read-only  
DESCRIPTION  
  "read-create access is not required. This may be  
  read-only."

OBJECT            rsvpResvDestAddr  
MIN-ACCESS read-only  
DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT            rsvpResvSenderAddr  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be read-only."

OBJECT            rsvpResvDestAddrLength  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be read-only."

OBJECT            rsvpResvSenderAddrLength  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be read-only."

OBJECT            rsvpResvProtocol  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be read-only."

OBJECT            rsvpResvDestPort  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be read-only."

OBJECT            rsvpResvPort  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be read-only."

OBJECT            rsvpResvHopAddr  
MIN-ACCESS read-only  
DESCRIPTION  
"read-create access is not required. This may be read-only."

OBJECT            rsvpResvHopLih  
MIN-ACCESS read-only  
DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvInterface

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvService

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvTSpecRate

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvTSpecPeakRate

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvTSpecBurst

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvTSpecMinTU

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvTSpecMaxTU

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvRSpecRate

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvRSpecSlack

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvInterval

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvScope

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvShared

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvExplicit

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvRSVPHop

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvPolicy

MIN-ACCESS read-only

DESCRIPTION

"read-create access is not required. This may be read-only."

OBJECT rsvpResvStatus

MIN-ACCESS read-only

DESCRIPTION

```

        "read-create access is not required.  This may be
        read-only."
OBJECT      rsvpResvFlowId
MIN-ACCESS not-accessible
DESCRIPTION
    "This object is needed only in a system that imple-
    ments IPv6."

OBJECT      rsvpResvFwdStatus
MIN-ACCESS read-only
DESCRIPTION
    "read-create access is not required.  This may be
    read-only."

OBJECT      rsvpResvFwdFlowId
MIN-ACCESS not-accessible
DESCRIPTION
    "This object is needed only in a system that imple-
    ments IPv6."

 ::= { rsvpCompliances 1 }

rsvpSessionGroup OBJECT-GROUP
    OBJECTS {
        rsvpSessionType, rsvpSessionDestAddr,
        rsvpSessionDestAddrLength, rsvpSessionProtocol,
        rsvpSessionPort, rsvpSessionSenders, rsvpSessionReceivers,
        rsvpSessionRequests
    }
    STATUS current
    DESCRIPTION
        "These objects are required for RSVP Systems."
    ::= { rsvpGroups 1 }

rsvpSenderGroup OBJECT-GROUP
    OBJECTS {
        rsvpSenderType, rsvpSenderDestAddr, rsvpSenderAddr,
        rsvpSenderDestAddrLength, rsvpSenderAddrLength,
        rsvpSenderProtocol, rsvpSenderDestPort, rsvpSenderPort,
        rsvpSenderHopAddr, rsvpSenderHopLih, rsvpSenderInterface,
        rsvpSenderTSpecRate, rsvpSenderTSpecPeakRate,
        rsvpSenderTSpecBurst, rsvpSenderTSpecMinTU,
        rsvpSenderTSpecMaxTU, rsvpSenderInterval,
        rsvpSenderLastChange, rsvpSenderStatus,
        rsvpSenderRSVPHop, rsvpSenderPolicy,
        rsvpSenderAdspecBreak, rsvpSenderAdspecHopCount,
        rsvpSenderAdspecPathBw, rsvpSenderAdspecMinLatency,

```

```

    rsvpSenderAdspecMtu, rsvpSenderAdspecGuaranteedSvc,
    rsvpSenderAdspecGuaranteedBreak,
    rsvpSenderAdspecGuaranteedCtot,
    rsvpSenderAdspecGuaranteedDtot,
    rsvpSenderAdspecGuaranteedCsum,
    rsvpSenderAdspecGuaranteedDsum,
    rsvpSenderAdspecGuaranteedHopCount,
    rsvpSenderAdspecGuaranteedPathBw,
    rsvpSenderAdspecGuaranteedMinLatency,
    rsvpSenderAdspecGuaranteedMtu, rsvpSenderAdspecCtrlLoadSvc,
    rsvpSenderAdspecCtrlLoadBreak,
    rsvpSenderAdspecCtrlLoadHopCount,
    rsvpSenderAdspecCtrlLoadPathBw,
    rsvpSenderAdspecCtrlLoadMinLatency,
    rsvpSenderAdspecCtrlLoadMtu, rsvpSenderNewIndex
}
STATUS current
DESCRIPTION
    "These objects are required for RSVP Systems."
 ::= { rsvpGroups 2 }

```

rsvpResvGroup OBJECT-GROUP

```

    OBJECTS {
        rsvpResvType, rsvpResvDestAddr, rsvpResvSenderAddr,
        rsvpResvDestAddrLength, rsvpResvSenderAddrLength,
        rsvpResvProtocol, rsvpResvDestPort, rsvpResvPort,
        rsvpResvHopAddr, rsvpResvHopLih, rsvpResvInterface,
        rsvpResvService, rsvpResvTSpecRate, rsvpResvTSpecBurst,
        rsvpResvTSpecPeakRate, rsvpResvTSpecMinTU,
        rsvpResvTSpecMaxTU, rsvpResvRSpecRate,
        rsvpResvRSpecSlack, rsvpResvInterval,
        rsvpResvScope, rsvpResvShared, rsvpResvExplicit,
        rsvpResvRSVPHop, rsvpResvLastChange, rsvpResvPolicy,
        rsvpResvStatus, rsvpResvNewIndex
    }
STATUS current
DESCRIPTION
    "These objects are required for RSVP Systems."
 ::= { rsvpGroups 3 }

```

rsvpResvFwdGroup OBJECT-GROUP

```

    OBJECTS {
        rsvpResvFwdType, rsvpResvFwdDestAddr, rsvpResvFwdSenderAddr,
        rsvpResvFwdDestAddrLength, rsvpResvFwdSenderAddrLength,
        rsvpResvFwdProtocol, rsvpResvFwdDestPort, rsvpResvFwdPort,
        rsvpResvFwdHopAddr, rsvpResvFwdHopLih, rsvpResvFwdInterface,

```

```

    rsvpResvFwdNewIndex, rsvpResvFwdService,
    rsvpResvFwdTSpecPeakRate, rsvpResvFwdTSpecMinTU,
    rsvpResvFwdTSpecMaxTU, rsvpResvFwdTSpecRate,
    rsvpResvFwdTSpecBurst, rsvpResvFwdRSpecRate,
    rsvpResvFwdRSpecSlack, rsvpResvFwdInterval,
    rsvpResvFwdScope, rsvpResvFwdShared, rsvpResvFwdExplicit,
    rsvpResvFwdRSVPHop, rsvpResvFwdLastChange,
    rsvpResvFwdPolicy, rsvpResvFwdStatus
}
STATUS current
DESCRIPTION
    "These objects are optional, used for some RSVP
    Systems."
 ::= { rsvpGroups 4 }

```

```

rsvpIfGroup OBJECT-GROUP
    OBJECTS {
        rsvpIfUdpNbrs, rsvpIfIpNbrs, rsvpIfNbrs, rsvpIfEnabled,
        rsvpIfUdpRequired, rsvpIfRefreshBlockadeMultiple,
        rsvpIfRefreshMultiple, rsvpIfRefreshInterval, rsvpIfTTL,
        rsvpIfRouteDelay, rsvpIfStatus
    }
STATUS current
DESCRIPTION
    "These objects are required for RSVP Systems."
 ::= { rsvpGroups 6 }

```

```

rsvpNbrGroup OBJECT-GROUP
    OBJECTS {
        rsvpNbrProtocol, rsvpNbrStatus
    }
STATUS current
DESCRIPTION
    "These objects are required for RSVP Systems."
 ::= { rsvpGroups 7 }

```

```

rsvpNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS { newFlow, lostFlow }
STATUS current
DESCRIPTION
    "This notification is required for Systems sup-
    porting the RSVP Policy Module using an SNMP
    interface to the Policy Manager."
 ::= { rsvpGroups 8 }

```

END

#### 4. Security Considerations

The use of an SNMP SET results in an RSVP or Integrated Services reservation under rules that are different compared to if the reservation was negotiated using RSVP. However, no other security considerations exist other than those imposed by SNMP itself.

#### 5. Authors' Addresses

Fred Baker  
Postal: Cisco Systems  
519 Lado Drive  
Santa Barbara, California 93111

Phone: +1 805 681 0115  
EMail: fred@cisco.com

John Krawczyk  
Postal: ArrowPoint Communications  
235 Littleton Road  
Westford, Massachusetts 01886

Phone: +1 508 692 5875  
EMail: jjk@tiac.net

Arun Sastry  
Postal: Cisco Systems  
210 W. Tasman Drive  
San Jose, California 95134

Phone: +1 408 526 7685  
EMail: arun@cisco.com

#### 6. Acknowledgements

This document was produced by the RSVP Working Group.

## 7. References

- [1] Rose, M., Editor, "Management Information Base for Network Management of TCP/IP-based internets", STD 17, RFC 1213, May 1990.
- [2] Information processing systems - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1), International Organization for Standardization. International Standard 8824, (December, 1987).
- [3] Information processing systems - Open Systems Interconnection - Specification of Basic Encoding Rules for Abstract Notation One (ASN.1), International Organization for Standardization. International Standard 8825, (December, 1987).

